



WOODguard®

WOODguard is a one coat, penetrating stain and EPA registered wood preservative. It contains copper 8, which is toxic to termites and anobiid powderpost beetles. It also contains UV blockers and has vigorous water repellency and is VOC compliant in all 50 states.

Wood should be washed with a TSP and bleach solution prior to WOODguard application to insure there is no mill glaze to impede penetration. See Preparation and Maintenance Guide referenced below.

Best application is achieved using a backpack sprayer to flood the wood then back brush to point of refusal. Brushing is important to work the WOODguard into the wood for maximum penetration. Do not apply more than one coat.

Do not apply with an airless sprayer.

Coverage should be 150–300 ft² gal on initial coat on new wood. If you cover more than 300 ft² per gal suspect a mill glaze issue.

WOODguard goes on dark and can take up to a month or more to achieve final color.

WOODguard clear will have a slight green tint when applied due to the copper. Most of this will disappear over time.

Sides of home in full sun may require re-treatment before shaded sides. Typically after the initial coat WOODguard should be re-applied after 18-24 months.

WOODguard will last longer after each additional application. You should get 3-5 years of protection after second application.

WOODguard contains a moldicide, but additional moldicide is recommended for homes near water or heavily forested homesites.

Please refer to WOODguard Preparation and Maintenance Guide for complete instructions available at www.iskbiocides.com/residential/woodguard.php.

WOODguard®

ISK BIOCIDES, INC.
Innovation With Integrity®

Toll Free: 1-800-238-2523
Fax: 901-344-5388
info@iskbiocides.com

Woodguard® is a registered trademark of IBC Manufacturing Company
Innovation With Integrity® is a registered trademark of ISK Americas Incorporated
ISK® is a registered trademark of Ishihara Sangyo Kaisha, Ltd.