

PRODUCT DATA SHEET

WOODGUARD® SWO

(SWEDISH WOOD OIL™)
ESPECIALLY FOR PRESSURE-TREATED WOOD

PRODUCT DESCRIPTION AND BASIC USE

WOODguard® SWO is a clear, water repellent that helps retard warping, cupping, splitting and nail popping. Especially designed for pressure-treated lumber. Restores lubricity lost in wood during pressure treatment. Will never crack or peel.

WOODguard SWO is a colorless, water-repellent treatment for pressure-treated wood. Pressure treatment effectively preserves wood against insect attack and degradation from mold and fungal growths. It is not, however, immune from the damaging effects of water. Pressure treatment causes wood to become highly porous and water absorbent. In winter, water will freeze in the pores of the wood cell structure and then thaw, eventually causing the wood to become brittle. Direct sun and heat of summer further dry the wood, which eventually warps and splits long before it ever rots from decay.

FEATURES

WOODguard SWO is absorbed into the wood and bonds with the cell structure. The oils lubricate and stabilize the wood while repelling water. It helps retard warping, cupping, splitting and nail popping. One moderate coat promotes dimensional stability, and special penetrating oils restore the natural lubricity of the wood often lost in the pressure-treating process. Woodguard SWO is recommended for use on pressure treated wood decks, fences, storage buildings and all other pressure-treated wood construction projects.

COLOR

WOODguard SWO dries into the wood and does not provide any color. Application of WOODguard SWO will give wood an oiled appearance which weathers out to a silvery grey color over time. Most alkyd/oil-based stains can be applied over WOODguard SWO after two weeks minimum cure period. It is best to apply this dual treatment first to a small, remote surface in order to verify compatibility. Do not attempt to apply latex finishes/stains over WOODguard SWO. **DO NOT TINT!**

AVAILABILITY

WOODguard SWO is available in 1 gallon cans (4 x 1 gallon case) and 5 gallon pails. Visit our website or call 800-238-2523 for the dealer nearest you.

EXPERT ADVICE

Consult our Woodguard Expert Advisors for the best advice for your situation.

Blairstown Distributors @ www.Blairstowndistributors.com | ph: 1-800-524-1093

Twin Creeks Log Homes @ www.twincreeksloghomes.com | ph: 1-800-299-8981

APPLICATION

WOODguard SWO is easy to use. It can be brushed, rolled or sprayed. Apply above 50° F for fastest cure time. (Below 50° F, WOODguard SWO may become too viscous to spray). One moderate coat is sufficient. Do not over apply. Use only as much as can be readily absorbed by the wood. Surfaces should be cleaned and free of all loose debris. When using wood that has not been kiln dried, wait six months after construction before treating for maximum penetration. Moisture content of wood should be less than 18%.

SUBSEQUENT TREATMENTS

WOODguard SWO can be re-applied when the surface exhibits signs of water absorption.

COVERAGE

250 - 300 sq. ft/gal depending on surface condition and wood porosity.

HANDLING AND STORAGE

KEEP OUT OF REACH OF CHILDREN

Do not handle until all safety precautions have been read and understood. See product label and Safety Data Sheet for hazards and precautions.

Observe good personal hygiene practices. Change protective gloves/clothing when signs of contamination appear.

COMBUSTIBLE: Store in a secure, well-ventilated area protected from extreme temperatures. Do not transfer to an unmarked container. Keep container closed when not in use. Do not store or use in the vicinity of sparks, open flame, or other ignition sources. Do not smoke while using this product.

For product emergencies, call Chemtrec toll free at 1-800-424-9300.

DISPOSAL

Very toxic to aquatic life. Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

TECHNICAL DATA

Appearance	Clear to hazy light yellow liquid
Viscosity	20-30 CpS Brookfield #1 @ 20 rpm @ 70°F
Flash Point	164°F PMCC
pH	Not applicable
VOC	224 g/L – 1.87 lbs/gal

WARRANTY AND LIMITATION OF DAMAGES

Seller warrants to those persons lawfully acquiring title to this product that at the time of the first sale of this product by seller this product conformed to its chemical description and that it was reasonably fit for the purposes stated on the product label when used both in accordance with the Directions for Use appearing on the product label and under normal conditions of use. Buyers and users of this product assume the risk of all loss or damage from use or handling of this product that results from their failure to read and comply with the Directions for Use of this product, which appear on the product label. **SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR OF MERCHANTABILITY, AND NO AGENT OF SELLER IS AUTHORIZED TO DO SO.** Unless expressly prohibited by state law, the liability of seller for any breach of warranty shall not exceed the purchase price of the product as to which a claim is made.

All information contained in this bulletin is furnished by ISK Biocides, Inc. free of charge for your evaluation and is for informational purposes only. No guarantee, expressed or implied, is made by ISK Biocides, Inc. as to the results to be obtained based upon your use of the information. ISK Biocides, Inc. expressly disclaims any liability, foreseen or unforeseen, arising out of your use of the information. This information should not be treated as absolutely complete since additional information may be necessary or desirable when particular, exceptional or variable conditions or circumstances exist or because of applicable laws or government regulations. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent or trademark or violate any law or regulation.

WOODguard® is a registered trademark of IBC Manufacturing Company.
Swedish Wood Oil™ is a trademark of ISK Americas Incorporated