

WOOD guard® D&L

DECK & LOG™



EXTERIOR OIL-BASED STAIN

THE SUPERIOR PENETRATING STAIN IDEALLY SUITED FOR
DECKS, LOGS, RAILINGS AND PILINGS

Manufactured for:

ISK Biocides, Inc.

416 East Brooks Road • Memphis, TN 38109

IBD-PL-1093

02/26

Woodguard® is a registered trademark of IBC Manufacturing Company.

MEETS ALL STATE VOC REQUIREMENTS
VOLATILE ORGANIC COMPOUNDS <105 grams/liter

WOOD guard® D&L

THE SUPERIOR PENETRATING STAIN IDEALLY SUITED FOR DECKS, LOGS, RAILINGS AND PILINGS

WARNING

Combustible liquid.
Causes serious eye irritation.



Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking.
Wear protective gloves, clothing, eye, and face protection. Wash hands thoroughly after handling. Do not touch eyes. In case of fire: Use suitable extinguishing media to extinguish.

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get emergency medical help. Store in a well-ventilated place.

Do not contaminate water, food or feed by storage or disposal.

Store in a secure, dry, well-ventilated area protected from extreme temperatures.

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

FOR AN EMERGENCY, CALL 911.

For non-emergency, product related assistance, call CHEMTREC toll free at 800-424-9300. Have the product container or label with you when receiving assistance or medical treatment.

PRODUCT DESCRIPTION

WOODguard Deck & Log is a heavy-duty, tintable treatment designed for protecting decks and other wood surfaces. It does not form a film and will never crack or peel. It does not "DRY" in the conventional sense. It cures into the wood.

Treated lumber is prone to rapid moisture gains and losses that cause warping and splitting in many wood species. Each changing season causes dimensional stress that can splinter and physically damage a wooden deck or log.

WOODguard Deck & Log is a water repellent, wood stabilizer that highlights natural wood tones. It restricts cupping, warping, and splitting. It minimizes physical deterioration caused by dimensional instability resulting from water absorption and extreme humidity changes. Treatment with WOODguard Deck & Log also helps reduce nail corrosion and popping.

DIRECTIONS FOR USE

Apply to dry wood, with no more than 20% moisture content. This will achieve maximum penetration and the fastest drying of the product.

New or weathered wood must be cleaned prior to WOODGUARD Deck & Log application. See Preparation and Maintenance Guide for directions, which is available at www.iskbiocides.com.

Coverage is typically 100-250 sq. ft / gallon, depending on surface condition and wood porosity. One moderate coat of WOODguard Deck & Log is sufficient.

Apply liberally by simply wetting down the surface as follows:

- Spray:** Use a sprayer with an adjustable nozzle. Set the nozzle to deliver a low pressure, coarse spray and back brush as necessary.
- Brush:** A regular paint brush is fine for most surfaces. For uneven shingles or rough surfaces, use a stiff bristle brush. Apply evenly, brushing out sags, etc. as necessary.
- Roller:** Use a long nap if applying to rough surfaces.

Promptly clean all tools, rags, etc. with detergent and water. If WOODguard Deck & Log has cured, mineral spirits or paint thinner should be used for cleaning.

Blot up any excessive WOODguard Deck & Log left unabsorbed on the application surface after 24hrs.

Manufactured for:

ISK Biocides, Inc.

416 East Brooks Road • Memphis, TN 38109

Must Read Before Use:

- Avoid contact with plants, shrubs and trees.
- Before full application of WOODguard Deck & Log, test the product on a small, indiscrete area to verify product penetration and preferred color. Do not apply to painted, sealed, or highly dense surfaces.
- Stir or shake well before use. When using WOODguard Deck & Log, manually stir or mechanically mix to ensure even pigment distribution and even color. Stir frequently when applying to keep pigments evenly dispersed and uniform. Coat surfaces evenly.
- WOODguard Deck & Log Base may be tinted with either oil based or universal colorants ONLY. Do not add more than 4 ounces of colorant per gallon. Do not add tint to pre-tinted WOODguard Deck & Log
- If using in a shady or high moisture area, additional protection can be obtained by adding a compatible mildewcide to the WOODguard Deck & Log and mixing well.
- Apply when temperature is above 50°F. Hot weather promotes a faster cure time. Below 50°F, WOODguard Deck & Log may become too viscous to spray.
- Do not apply if rain is expected within 36 hours.
- Avoid contact with asphalt (including asphalt shingles).
- Avoid open flame during application and until WOODguard Deck & Log has thoroughly penetrated the treated surface and any excess has been removed.
- Until thoroughly cured, the area treated may be slippery.
- WOODguard Deck & Log may be applied to newly constructed, pressure-treated decks that are dry.
- WOODguard Deck & Log has a highly water repellent system that will repel latex coatings and may not be compatible with some oil or alkyd coatings. Any subsequent coating applied over WOODguard Deck & Log should be tested on a small area to verify effectiveness before application.

WARRANTY AND LIMITATION OF DAMAGES

Seller warrants to those persons lawfully acquiring title to this product that at the time of the first sale of this product by seller this product conformed to its chemical description and that it was reasonably fit for the purposes stated on the product label when used both in accordance with the Direction for Use appearing on the product label and under normal conditions of use. Buyers and users of this product assume the risk of all loss or damage from use or handling of this product that results from their failure to read and comply with the Directions for Use of this product which appear on the product label. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR OF MERCHANTABILITY, AND NO AGENT OF SELLER IS AUTHORIZED TO DO SO. Unless expressly prohibited by state law, the liability of seller for any breach of warranty shall not exceed the purchase price of the product as to which a claim is made.